



**FERRARI**



**CHARGER**

# Series



# Portable Level 2 EV Charger 9.6kW



## Specifications

Power	9.6KW
Input/Output	240VAC/240VAC
Output current	40A
Over temperature protection	≥95°C
Rated residual operating current	CCID20
Operating temperature	'-30°C- +50°C
Storage temperature	'-40°C- +85°C
Relative humidity	5%~95% No condensation
Life time of connector	≥10000 times
Mean time between failure	MTBF≥3000h
Metal wire sectional area	8.37mm <sup>2</sup>
Maximum altitude	2000m
Connector type	SEA J1772 Type 1
Power plug	NEMA14-50
Cable length	5 meters (Customizable)
Weight	4 Kg (with cable)
Indicator lights	Power/connect/charging/error
Protection	Connector IP54, Host IP66 & IK10
Host dimension	255*96*63(mm)

# Series



# Wall-Mount AC EV Charger 7.2kW



## Specifications

Power	7.2KW
Input/Output	230VAC/230VAC
Output current	32A
Over temperature protection	≥95°C
Rated residual operating current	AC30mA+DC6mA
Operating temperature	'-30°C- +50°C
Storage temperature	'-40°C- +85°C
Relative humidity	5%~95% No condensation
Life time of connector	≥10000 times
Mean time between failure	MTBF≥8796h
Start method	Plug and play/RFID card/App
Maximum altitude	2000m
Communication	WIFI+BLE/4G Optional
Connector type	IEC 62196-2 Type 2
Cable length	5 meters (Customizable)
Weight	5 Kg (with cable)
Wiring method	Enter and out at the bottom
Protection	Connector IP54, Host IP66 & IK10
Host dimension	353*256*113(mm)